


200W




COLOR CODE	SL
PART NUMBER	GRW-120-48-200-SL-S-C
ORDER CODE	70-1002
PERFORMANCE	
WATTS (MAX)	200
PPF	488
PPE	2.5
POWER INPUT	100~277VAC 50/60Hz
COLOR RANGE (nm)	400-700
UV	NO
FAR RED	NO
SPECTRUM BOOSTER	N/A
FACTORY DEFAULT RATIO	6:1
BEST RATIO RANGE	1:1~10:1
CONTROLS	
DIMMING	YES
CONTROL BOX	YES
APP	YES
BLUETOOTH®	NO
WIFI	YES
LYNX3™	NO
SMARTUNE™	NO
PHYSICAL STATS	
COOLING	PASSIVE, FANLESS COOLING
DIMENSIONS	1240mm x 140mm x 76 mm (48.4" x 5.5" x 3.0")
WEIGHT	6.35 kg (14 lbs)
IP RATING	IP66
CERTIFICATIONS	
UL	YES
DLC	YES
WARRANTY	5 YEARS
RATED LIFETIME	L70 50,000 Hours

The BenchLight™ SL (Sunlight) model is designed to mimic the visible PAR range of the sun. Suitable for applications from 1-foot to 4-foot installations. This model is designed to produce the same color profile of visible sunlight. However, it is fully adjustable with the controller and APP technology.

Full control of the color ratio and intensity, through the Grow3™ Controller. The SL model is designed for best operation between 1:1 to 10:1 ratios while maintaining a steady PPE.



COLOR RATIO EXAMPLE



EXAMPLE: DEFAULT COLOR RATIO 6:1 AT 100% ILLUMINANCE

INCLUDED WITH LIGHT FIXTURE



74-1001 - POWER CABLE, 1.5M



75-1002 - HANGING KIT, 2M (2PCS)

OPTIONAL ACCESSORIES*



72-1001 - GROW3, CONTROLLER



74-1002 - 0.5M SIGNAL CABLE

*Most common accessories shown, contact LED Smart for full list of available accessories.